

CFS Foot Switch



Features

- Metal series shell
- Plastic series shell

Contact Form



Features

Designation	Model	Rating	Type of switch enclosed & contact arrangement	Cable type / length	Cantact	Action force	Material of Rind
Standard type Momentary Action	CFS-101	10A 250VAC	CMV-100D	0.75mm ² ,3C/0.5 meter ,1 meter~3 meter	1A1B	1.2kg	Plastic
	CFS-102	15A 250VAC	CM-1704	0.75mm ² ,3C/1 meter ,1.5 meter ~2 meter	1A1B	1.1kg	
	CFS-2	10A 250VAC	CMV-100D	0.5mm ² ,3C/1 meter~3 meter	1A1B	1.1kg	Aluminum Cast
	CFS-3	10A 250VAC	CMV-100D	0.75mm ² ,3C/0.5 meter,1 meter~3 meter	1A1B	1.2kg	
	CFS-3S	15A 250VAC	CM-1704	0.75mm ² ,3C/1 meter,1 meter ~3 meter	1A1B	1.1kg	
Alternate action	CFS-105	6A 250VAC	CS-105	0.75mm ² ,2C/1 meter,1 meter ~2 meter	PUSH ON PUSH OFF	2kg	Plastic
	CFS-305	6A 250VAC	CS-105	Accessory: Cable gland (No cable)		3.1kg	Aluminum Cast
	CFS-405	6A 250VAC	CS-105			3.1kg	
	CFS-505	6A 250VAC	CS-105			3.1kg	
Mini foot switch Front end push	CFS-201	10A 250VAC	CMV-100D	0.5mm ² ,3C/1 meter ~3 meter	1A1B	0.7kg	Plastic
	CFS-01	10A 250VAC	CMV-100D	0.5mm ² ,3C/1 meter ~3 meter	1A1B	0.7kg	
	CFS-1	10A 250VAC	CMV-100D	0.5mm ² ,3C/1 meter ~3 meter	1A1B	0.9kg	Iron
Protective guard foot switch	CFS-302	15A 250VAC	CM-1704	Accessory: Cable gland (No cable)	1A1B	3.2kg	Aluminum Cast
	CFS-304	15A 250VAC	CM-1704 * 2		2A2B	3.2kg	
	CFS-502	15A250VAC	CM-1704		1A1B	3.2kg	
	CFS-504	15A250VAC	CM-1704 * 2		2A2B	3.2kg	
	CFS-602	15A250VAC	Button spring type		2*1A1B	2.8kg	
	CFS-702	15A250VAC	CM-1704		2*1A1B	3.2kg	
Large type	CFS-402	15A250VAC	CM-1704		1A1B	3.2kg	
	CFS-404	15A 250VAC	CM-1704 * 2		2A2B	3.2kg	
	CFS-802	15A 250VAC	CM-1704		2*1A1B	3.2kg	